

RECEIVED
CENTRAL FAX CENTER

MAR 24 2010

Amendments to the Claims

1. (currently amended) A method of manufacturing that involves a plurality of companies at different locations, the method comprising:
 - developing, ~~via~~ by a computer system, an electronic specification describing a product and a plurality of components thereof;
 - inducing the plurality of companies to manufacture the plurality of components, wherein the step of inducing the plurality of companies to manufacture the plurality of components includes forwarding the electronic specification to a specific company that is one of the plurality of companies;
 - inducing the specific company to build the product or a component thereof in accordance with a plurality of requirements in the electronic specification, wherein the component is one of the plurality of components;
 - the specific company building the product or the component thereof in accordance with the plurality of requirements in the electronic specification;
 - after the specific company building the product or component thereof, testing the product or the component thereof;
 - upon testing the product or component thereof, creating an operability test result;
 - appending, via ~~by~~ the computer system, the operability test result to the electronic specification, thereby creating an appended operability test result;
 - inducing the specific company to determine if the product or the component thereof is completed;
 - inducing the specific company to forward the electronic specification with the appended operability test result to another one of the plurality of companies; and
 - assembling the plurality of components to produce the product.
2. (original) The method of claim 1 wherein the forwarding step includes the step of providing a central server to centralize the forwarding step.
3. (original) The method of claim 2 including the further step of providing a bill of materials for the components and the product at the time the electronic specification is developed.
4. (original) The method of claim 3 including the further step of periodically comparing the bill of materials to the electronic specification to verify the accuracy of both.

5. (original) The method of claim 4 including the further step of saving at least one updated version of the electronic specification.

6. (original) The method of claim 5 including the further step of comparing the updated version of the electronic specification with an electronic specification having appended test results.

7. (currently amended) The method of claim 5 including the further step of after the specific company building the product or component thereof, revising the updated version to include late customer changes.

8. (original) The method of claim 7 including the further step of comparing the revised updated version of the electronic specification with an electronic specification having appended test results; wherein the comparing step includes the steps of determining and implementing late customer changes to the electronic specification in the product or components.

9. (canceled)

10. (currently amended) A method of doing business comprising: ~~via~~ by a computer system, generating a sales order representative of a product wherein the product includes a communications bus and input and output components to be operably linked to the bus; developing, ~~via~~ by the computer system, build and test instructions from the sales order; developing, ~~via~~ by the computer system, an installation sequence from the build and test instructions; and building the product using the build and test instructions in the sequence laid out by the installation sequence; wherein the building step includes the further steps of: calling for an input or output component to be operably connected to the communication bus as identified by the installation sequence; verifying the operability of the components and the bus; receiving the first signal from the component by means of the bus; determining a unique identify for the signaling component; and responding, by means of the bus, with a second signal to the component providing the component with an identity.

11. (original) The method of claim 10 wherein the developing and building steps are performed under the control of a control device.

12. (canceled)

13. (previously presented) The method of claim 10 wherein the developing an installation sequence step is accomplished by a tester device which also oversees the building step.

14. (canceled)

15. (canceled)

16. (previously presented) The method of claim 10 wherein the responding step further includes the step of providing the signaling component with operational parameters.

17. (original) The method of claim 16 wherein the generating step includes the further step of creating a bill of materials and a specification.

18. (original) The method of claim 17 wherein the developing the build and test instruction step includes the further step of using the specification to create a build and test file.

19. (original) The method of claim 18 wherein the build and test file is in the xml format.

20. (original) The method of claim 19 wherein the installation sequence developing step includes the further step of cross checking the installation sequence with the specification.

21. (original) The method of claim 20 wherein the installation developing sequence includes a further step of cross checking the bill of materials with the installation sequence.

22. (original) The method of claim 21 wherein the verifying step includes the further steps of testing the operation of the communications bus, testing the operation of the component, and cross checking the identity, parameters and operation of the component and the bus with the specification.

Claims 23 – 31 (canceled)

32. (withdrawn) A method of building a product comprising the steps of: creating an electronic build document cataloging the features and requirements for the product; forwarding the electronic build document to at least one component manufacturer, each component manufacturer building one or more components, testing the operability of said one or more components, and attaching the test results to the electronic build document to create a modified electronic build document; forwarding the modified electronic build document to a final assembly location wherein the one or more components and other materials are assembled into the product; testing the assembled product; and attaching the test results for the assembled product to the modified electronic build file to create a final electronic build file.

33. (withdrawn) The method of claim 32 including the further step of creating component records from the test results of the final electronic build file.

34. (withdrawn) The method of claim 32 wherein the creating step includes the further step of creating a duplicate electronic build document.

35. (withdrawn) The method of claim 34 including the further steps of updating the duplicate electronic build document with late customer changes and comparing the modified electronic build file with the updated duplicate electronic build document to verify and implement the late customer changes.

36. (withdrawn) The method of claim 32 wherein the testing step includes the further steps of: analyzing a signal on a power line to determine a quality thereof; analyzing a signal on a communications line to determine a quality thereof; generating a power analysis result signal as a function of the power line signal analysis; generating a communications line analysis result signal as a function of the communications line signal analysis; evaluating the results signals; and providing a comprehensive analysis of the power line, the communications line, the power line signal, the communications line signal, a communications bus, and any components attached thereto.

37. (withdrawn) The method of claim 32 wherein the testing step includes the further steps of: attaching a tester controller to a bus; providing a path from the tester controller to a technician; instructing, on the path, the technician to attach a specific one of a plurality of components to the bus; signaling, with a first signal from the technician to the tester controller, upon completion of the component attachment; signaling, with a

second signal from the tester controller to the technician, to confirm receipt of the first signal; causing a subcontroller to signal a main controller with a third signal; and configuring, upon receipt of the third signal, the subcontroller by transmitting configuration instructions from the main controller to the subcontroller over the bus.

38. (withdrawn) A method of doing business comprising the steps of: electronically creating a customer order which includes the requirements and components for a product desired by the customer; developing a bill of materials from the electronic order detailing the parts and materials required to build the product; developing an electronic specification from the customer order detailing the components, subassemblies and product required by the customer; sequentially transmitting the specification to the manufacturer of each component, assembly and final assembly, each manufacturer building the requisite component, subassembly or assembly, each manufacturer testing the requisite component, subassembly or assembly, and each manufacturer attaching the test results to the electronic specification; and periodically checking the electronic bill of materials versus the electronic specification to verify the compatibility and accuracy thereof.

39. (withdrawn) The method of claim 38 wherein one of the components includes a communication system having a bus and including the further steps of: guiding a technician in manufacturing the communication system; attaching a tester controller to the bus; providing a path from the tester controller to the technician; instructing, on the path, the technician to attach a specific one of the plurality of components to the bus; signaling, with a first signal from the technician to the tester controller, upon completion of the component attachment; signaling, with a second signal from the tester controller to the technician, to confirm receipt of the first signal; causing a subcontroller to signal a main controller with a third signal; and configuring, upon receipt of the third signal, the subcontroller by transmitting configuration instructions from the main controller to a subcontroller over the bus.

40. (withdrawn) The method of claim 39 wherein each component includes a control portion and a functional portion with an operational link therebetween and including the further steps of: verifying the operability of the communications bus by means of a tester controller; initiating, under the direction of the tester controller, a request that one of the plurality of components be attached to the bus; receiving the signal from the newly connected component by means of the communications bus; analyzing the communications bus and the newly connected component for operability; and responding

to signal from the newly connected component by means of the communications bus with instructions providing an identity and operating parameters to the newly connected component.

41. (withdrawn) The method of claim 40 wherein the initiating step includes the further steps of: causing the desired component to send the message on the communications bus; waiting for the message from the newly connected component; and recognizing the signal.

42. (withdrawn) A method of manufacturing a control system for an industrial or a process unit comprising: providing a plurality of components, each component including a control portion and a functional portion with an operational link therebetween; installing a communications bus on the unit; verifying the operability of the communications bus by means of a tester device; initiating, under the direction of the tester device, a request that one of the plurality of components be attached to the bus; receiving the signal from the newly connected component by means of the communications bus; analyzing the communications bus and the newly connected component for operability; and responding to signal from the newly connected component by means of the communications bus with instructions providing an identity and operating parameters to the newly connected component.

43. (withdrawn) The method of claim 42 wherein the initiating step includes the further steps of causing the desired component to send the message on the communications bus, waiting for the message from the newly connected component; and recognizing the signal.

44. (withdrawn) The method of claim 43 wherein the causing step includes the further step of initiating a visual signal to a technician.

45. (withdrawn) The method of claim 43 wherein the causing step includes the further step of magnetically triggering the component.

46. (withdrawn) The method of claim 45 wherein the causing step includes the further step of transmitting a visual or audible signal to the technician so as to cause the technician to initiate the magnetic trigger.

47. (withdrawn) The method of claim 46 including the further step of operating the

components in accordance with the identity and operating parameters.

48. (withdrawn) The method of claim 42, the communications bus including a power line and a communications line, wherein the analyzing step includes the steps of: analyzing a signal in the power line to determine a quality thereof; analyzing a signal on the communications line to determine a quality thereof; generating a power analysis result signal as a function of the power line signal analysis; generating a communications line analysis result signal as a function of the communications line signal analysis; receiving the power line and communications line result signals in a controller; evaluating the received signals; and providing a comprehensive analysis of the power line, the communications line, the power line signal, the communications line signal, communications bus, and any components attached thereto.

49. (withdrawn) A method of guiding a technician in manufacturing a communication system having a bus, a main controller, a plurality of components, and a subcontroller associated with each component; the method comprising the steps of: attaching a tester controller to the bus; providing a path from the tester controller to the technician; instructing, on the path, the technician to attach a specific one of the plurality of components to the bus; signaling, with a first signal from the technician to the tester controller, upon completion of the component attachment; signaling, with a second signal from the tester controller to the technician, to confirm receipt of the first signal; causing the subcontroller to signal the main controller with a third signal; and configuring, upon receipt of the third signal, the subcontroller by transmitting configuration instructions from the main controller to the subcontroller over the bus.

50. (withdrawn) The method of claim 49 wherein the causing step includes the further step of using a magnet to initiate the third signal from the subcontroller of the particular component.

51. (withdrawn) The method of claim 50 wherein the first signal is a wireless radio frequency signal and the second signal is an audible signal.

52. (withdrawn) The method of claim 49 wherein the first signal is a wireless radio frequency signal and the second signal is an audible signal.

Claims 53 – 59 (canceled)